

Splice cabinet T20



Part no.

11470300

Facts on splice cabinet T20

- For splicing fibre optic cables.
- Front also serves as a workbench when splicing fibres in multicassettes.
- Four hangers for multicassettes included.
- Multicassettes and holderblocks for cables are ordered seperately.
- Depending on the type of cable, 2 or more cables can be anchored to the back cover of the cabinet. Fibre is inserted into the supplied black protective hose.
- Intake for unbroken fibre cable. (Midspan)
- Cables can be places either from above or below in the cabinet. When laying cable, the right side of the cabinet is dimantled for increased accessibility.
- Console 11478440 mounted on the back, creating a space between the T20 and the wall. Existing cables on a wall for example. Installed T20 or other equipment does not constitute an obstacle to continued construction with several T20 above each other.
- Strain reliver external is used in cases where more cables than two are installed. Or when you want to perform the trasition from cable to protective hose outside the cabinet. In the strain reliver, 2 pcs 20 mm or

1 pcs 50 mm cable can be installed.

Capacity:

20 Multicassettes
3 pcs Cable holder

Mounting:

wall-mounted cabinet

Dimensions:

Hight: 300 mm
width: 600 mm
Depth: 300 mm

Material:

Powder coated aluzinc steel

Weight:

14 kg

Accessories and tools

Product	Part no.
Multicassette fibre organizer 36f, 2-pcs	11 202 202
Holder external 2x10 flex hose	11 478 052
Kit with 2 pcs of hanger for splice organizer	11 478 400
Cable holder for micro cable or cable with FRP	11 478 410
Holder for microducts 64x 4mm OD	11 478 418
Holder for microducts 64x 5mm OD	11 478 420
Holder for microducts 64x 7mm OD	11 478 422
Holder for tube T20/T80	11 478 425
Bracket splice cabinet T20	11 478 440
