

T240 OPGW Flipcassette



Facts about T240-OPGW Flipcassette

The T240-OPGW combines the trusted T240 closure with some accessories to handle cable retention and mounting on poles and towers. Your T240-OPGW can be equipped with numerous kinds of cable sealings, accessories, and mounts.

Flipcassette is an alternative fiber management option for applications where fibers are frequently re-routed between cassettes. It is designed to make reconfiguration easier and to provide a clear overview during re-entry. The T240-OPGW Flipcassette combines the since long proven T240 closure with the possibility to route the fibers without protection tubes.

Designed for frequent re-routing


Fibers are routed in side raceways and via a bottom mixer, making it easy to re-route fibers between cassettes when network changes require it.

Clear overview during service work

Hinged cassettes can be flipped through to quickly access specific cassettes and maintain an organized workspace.

Handles both crimp and shrink type splice protectors

The FlipCassette system is available for both crimp and shrink splice protectors.



Regional availability:

FlipCassette is not available in all markets. Please contact your local Tykoflex representative for current regional availability.

Number of splice cassettes:

18 cassettes

Splice capacity:

216 splices

Cable ports:

3 ports | 4 ports

Each port accommodates:

1x OPGW up to Ø29 mm

1x-12x drop cables depending on cable diameter

Contact Tykoflex for more information.